




Model No: 650783.5 ESX2
6.66" 7/8 Lobes 3.5 Stages




POWER SECTION


| ROTOR SPECIFICATIONS | | |
|----------------------|----------------------|--------|
| | Inch | mm |
| Overall Length | 252.0 | 6401 |
| Contour Length | 245.0 | 6223 |
| Eccentricity | 0.247 | 6.27 |
| Major Diameter | CONF | CONF |
| Head Diameter | 4.500 | 114.30 |
| Weight | 876 (lbs) 397.4 (kg) | |
| Material | 17-4SS | |
| Thread Form* | 2 7/8 API REG | |

| STATOR SPECIFICATIONS | | |
|-----------------------|-----------------------|-------|
| | Inch | mm |
| Overall Length | 260.0 | 6604 |
| Rubber Cut Back | 8.0 | 203 |
| Tube O.D. | 6.66 | 169.2 |
| Tube I.D. | 5.50 | 139.7 |
| Weight | 827 (lbs) 375 (kg) | |
| Number of Stages | 3.50 | |
| Rubber Type | NBR-HR | |
| Tube Material | 4 142 Seamless Tubing | |

| FIT INFORMATION | | |
|----------------------------|----------------|--------|
| NBR-HR | Minor Diameter | |
| Stator Size | Inch | mm |
| Undersize | | |
| Standard | 4.138 | 105.11 |
| Oversize | | |
| Nominal Fit at 75 F (25 C) | | |
| Undersize | | |
| Standard | 0.009 | 0.23 |
| Oversize | | |



| PERFORMANCE SPECIFICATIONS | | PERFORMANCE DETAILS | |
|----------------------------|---------------------------------------|----------------------------|-------------------|
| Torque Slope | 17.143 ft-lb/psi 3.371 Nm/kPa | Max Diff Press psi (kPa) | NBR-HR 790 (5430) |
| Flow Range | 300 to 600 GPM 1140 to 2270 Litre/min | Max Torque ft-lb (Nm) | 13500 (18300) |
| Rotation | 0.150 Rev/Gal 0.040 Rev/Litre | Stall Diff Press psi (kPa) | 1180 (8140) |
| Speed Range | 45 to 90 RPM | Stall Torque ft-lb (Nm) | 20250 (27450) |
| Off Bottom Press | 150 psi 1030 kPa | Max Recommended HP(kW) | 223 (166) |



Turning stator OD down below 6.66" is not recommended. Operating a power section above the maximum recommended differential pressure will reduce stator life. Performance Curves are for reference only. Actual power section performance may vary depending on the down hole temperature and rotor/stator fit. Performance data are subject to change without notice. Power calculation is based on maximum RPM and full torque. Stator sizes subject to change without notice. Copyright 2008 Dyna-Drill® Technologies, Inc. All rights reserved.